

Protect Cover 905 F3

coloris



**blanc
signalisation ral
9016**
905F3-31066



**ivoire clair ral
1015**
905F3-31076



**jaune de
sécurité ral
1003**
905F3-31061



**orangé pur ral
2004**
905F3-31063



**rouge carmin
ral 3002**
905F3-31065



**bleu ciel ral
5015**
905F3-31053



**ultramarine
blue ral 5002**
905F3-31051



**bleu gentiane
ral 5013**
905F3-31050



**vert opale ral
6026**
905F3-31055



**gris clair ral
7035**
905F3-31069



**gris agate ral
7038**
905F3-31071



**dust grey ral
7037**
905F3-31070



**noir foncé ral
9005**
905F3-31075

spécifications techniques

	valeur	norme
fil	2 × 1100 dtex PES HT	
poids	900 g/m ²	EN ISO 2286-2
laize	260 cm	
format standard pièce	± 30 ml / ± 300 ml	
résistance rupture (chaîne/trame)	400/400 daN/5 cm	EN ISO 1421
résistance déchirure (chaîne/trame)	45/45 daN	DIN 53.363
résistance au froid et au chaud	- 30°C / + 70°C	EN 4675

services

- Ajustement de la laize
- Coupe
- Tronçonnage
- Couleurs spéciales